

View Online at <https://aerobasegroup.com/nsn/5915-01-136-7939>

**Overall Length:**

Between 4.375 inches and 4.435 inches

**Body Outside Diameter:**

0.500 inches

**Vibration Resistance Range In Hertz:**

+5.0/+55.0

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**End Application:**

Test set, countermeasures an/usm-464

**Reference Frequency Per Function:**

600.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

94117

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

94117

**Output Terminal Identification:**

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:**

1.6 blank

**Average Power Rating Per Function:**

6.0 watts blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

300.00 megahertz blank and 500.00 megahertz blank and 700.00 megahertz blank and 1.00 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

500.00 megahertz blank and 700.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

500.0 megahertz blank and 700.0 megahertz blank

**Unpackaged Unit Weight:**

4.800 ounces

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0