## NSN 5915-01-141-0525

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-141-0525

Overall Length:
9.600 inches
Body Outside Diameter:
0.500 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Reference Frequency Per Function:
3.0 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.6 blank
Average Power Rating Per Function:
50.0 watts blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 terminal
Insertion Loss At Reference Frequency Per Function In Decibels:
0.7 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
500.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank and 4.00 gigahertz blank
Frequency Band Width Per Function:
2.00 gigahertz blank and 4.00 gigahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
50.0 blank and 50.0 blank and 1.0 blank and 1.0 blank
Voltage Standing Wave Ratio Frequency Limits Per Function:
2.0 gigahertz blank and 4.0 gigahertz blank
Unpackaged Unit Weight:
5.000 ounces
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## **NSN 5915-01-141-0525** High Pass Filter - Page 2 of 2



Fiig:

A047b0