NSN 5915-01-142-0387

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-142-0387

| Overall Height: |
|--|
| 7.000 inches |
| Body Length: |
| 12.000 inches |
| Body Width: |
| 8.000 inches |
| Body Height: |
| 4.000 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.253 inches and 0.262 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 11.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 8.250 inches |
| Operating Tempurature Range: |
| -18.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 10000.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms 4th radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 4th radio interference |

Power Line Frequency Rating Per Function In Hertz:

420.0 4th radio interference

Operating Current Rating Per Function In Amps:

40.0 3rd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd radio interference

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

4 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 4th radio interference 4th function

Thread Size:

0.190 inches

NSN 5915-01-142-0387

Radio Frequency Interference Filter - Page 2 of 2



| Unpackaged Unit Weight: |
|---|
| 30.000 pounds |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A047b0