Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-143-0444

Overall Length:
1.232 inches
Body Length:
0.550 inches
Body Outside Diameter:
0.385 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
1000.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
0.06 blank
Maximum Voltage Drop Per Function:
4.2 volts 23rd band suppression not specified
Principal Circuitry Type Per Function:
Capacitance-inductance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
28.0 volts dc blank
Thread Size:
0.250 inches
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
70.0 volts at sea level
Style Designator:
Round terminal/terminals on opposite surfaces

NSN 5915-01-143-0444

Radio Frequency Interference Filter - Page 2 of 2



Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-f-15733/24 government specification Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

A047b0