## NSN 5915-01-143-0909

Band Pass Filter - Page 1 of 2

Metal



View Online at https://aerobasegroup.com/nsn/5915-01-143-0909

| Overall Height:   |
|---|
| 2.875 inches  |
| Body Length:  |
| 1.625 inches  |
| Body Width:   |
| 1.625 inches  |
| Body Height:  |
| 2.375 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                          |
| 1.188 inches  |
| Vibration Resistance Range In Hertz:  |
| +10.0/+55.0   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                           |
| 1.188 inches  |
| Operating Tempurature Range:  |
| -0.0/+65.0 degrees celsius  |
| Average Life Rating In Hours:   |
| 10000.0   |
| Reference Frequency Per Function:   |
| 2.45 kilohertz blank  |
| Source Impedance Rating Per Function:   |
| 50.0 ohms blank   |
| Load Impedance Per Function:  |
| 50.0 ohms blank   |
| Principal Circuitry Type Per Function:  |
| Inductance-capacitance blank  |
| Mounting Facility Screw Thread Series Designator:   |
| Unc   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Type And Quantity:  |
| 4 threaded stud   |
| Insertion Loss At Reference Frequency Per Function In Decibels:                                       |
| 6.0 blank   |
| Functional Terminal Type And Quantity:  |
| 1 wire hook output 2nd function   |
| Specified Frequencies Of Discrimination Per Function:   |
| 2.425 kilohertz blank and 2.4375 kilohertz blank and 2.4625 kilohertz blank and 2.475 kilohertz blank |
| Thread Size:  |
| 0.138 inches  |
| Body Material:  |
| Matal   |

## NSN 5915-01-143-0909

Band Pass Filter - Page 2 of 2



Frequency Band Width Per Function:

2.4375 kilohertz blank and 2.4625 kilohertz blank

## Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0