NSN 5915-01-143-0912

Band Pass Filter - Page 1 of 2

Metal



View Online at https://aerobasegroup.com/nsn/5915-01-143-0912 **Overall Height:** 2.875 inches **Body Length:** 1.625 inches **Body Width:** 1.625 inches **Body Height:** 2.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.188 inches **Vibration Resistance Range In Hertz:** +10.0/+55.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.188 inches **Operating Tempurature Range:** -0.0/+65.0 degrees celsius **Average Life Rating In Hours:** 10000.0 **Reference Frequency Per Function:** 625.0 hertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank **Functional Terminal Type And Quantity:** 1 wire hook output 2nd function **Specified Frequencies Of Discrimination Per Function:** 600.00 hertz blank and 612.50 hertz blank and 637.50 hertz blank and 650.00 hertz blank **Thread Size:** 0.138 inches **Body Material:**

NSN 5915-01-143-0912

Band Pass Filter - Page 2 of 2



Frequency	Band	Width	Per	Function	n:
i i cauciic v	Dana	VVIGUI	1 61	i uncuoi	

612.50 hertz blank and 637.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0