

View Online at <https://aerobasegroup.com/nsn/5915-01-143-4946>

Overall Height:

2.875 inches

Body Length:

1.625 inches

Body Width:

1.625 inches

Body Height:

2.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.188 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.188 inches

Operating Temperature Range:

-0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

775.0 hertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 wire hook output 2nd function

Specified Frequencies Of Discrimination Per Function:

750.00 hertz blank and 762.50 hertz blank and 787.50 hertz blank and 800.00 hertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

762.50 hertz blank and 787.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0