

View Online at <https://aerobasegroup.com/nsn/5915-01-145-6071>

**Overall Length:**

1.202 inches

**Body Length:**

0.309 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

2.0 volts ac blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 20.0 and 40.0 and 60.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Width Across Flats:**

0.187 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 pin input 1st function1 pin output 2nd function

**Operating Voltage Rating And Type Per Function:**

200.0 volts ac blank

**Thread Size:**

0.164 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

400.0 volts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0