

View Online at <https://aerobasegroup.com/nsn/5915-01-148-3352>

Vibration Resistance Range In Hertz:

+5.0/+500.0

Operating Temperature Range:

-57.0/+71.0 degrees celsius

Reference Frequency Per Function:

35.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.4 blank

Inclosure Type:

Hermetically sealed

Insertion Loss At Reference Frequency Per Function In Decibels:

1.75 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 35.00 megahertz blank and 60.00 megahertz blank and 1.00 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 35.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 35.0 megahertz blank

Unpackaged Unit Weight:

0.400 ounces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0