

View Online at <https://aerobasegroup.com/nsn/5915-01-148-3352>

**Vibration Resistance Range In Hertz:**

+5.0/+500.0

**Operating Temperature Range:**

-57.0/+71.0 degrees celsius

**Reference Frequency Per Function:**

35.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.4 blank

**Inclosure Type:**

Hermetically sealed

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.75 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 35.00 megahertz blank and 60.00 megahertz blank and 1.00 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 35.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 35.0 megahertz blank

**Unpackaged Unit Weight:**

0.400 ounces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0