

View Online at <https://aerobasegroup.com/nsn/5915-01-151-2798>

Overall Height:

0.720 inches

Body Length:

2.150 inches

Body Width:

1.150 inches

Body Height:

0.560 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.005 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Reference Frequency Per Function:

10.7 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Voltage Standing Wave Ratio Per Function:

2.1 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 solder stud ground 3rd function

Specified Frequencies Of Discrimination Per Function:

10.40 megahertz blank and 10.67 megahertz blank and 10.703 megahertz blank and 11.00 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

10.67 megahertz blank and 10.703 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

10.67 megahertz blank and 10.703 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0