

View Online at <https://aerobasegroup.com/nsn/5915-01-151-2798>

**Overall Height:**

0.720 inches

**Body Length:**

2.150 inches

**Body Width:**

1.150 inches

**Body Height:**

0.560 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.005 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

+0.0/+65.0 degrees celsius

**Reference Frequency Per Function:**

10.7 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Crystal blank

**Voltage Standing Wave Ratio Per Function:**

2.1 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

2 solder stud ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

10.40 megahertz blank and 10.67 megahertz blank and 10.703 megahertz blank and 11.00 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

10.67 megahertz blank and 10.703 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

10.67 megahertz blank and 10.703 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0