## NSN 5915-01-151-2801

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-151-2801

Overall Length:
2.233 inches
Overall Height:
1.233 inches
Body Length:
2.000 inches
Body Width:
0.850 inches
Body Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.500 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-30.0/+105.0 degrees celsius
Reference Frequency Per Function:
500.0 hertz blank
Source Impedance Rating Per Function:
3.0 kilohms blank
Load Impedance Per Function:
1.0 megohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
2.0 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Maximum Dielectric Withstanding Ac Rms Voltage:
50.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
1.00 hertz blank and 1.00 kilohertz blank and 25.00 kilohertz blank and 50.00 kilohertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.00 hertz blank and 1.00 kilohertz blank

## NSN 5915-01-151-2801

Low Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 130.0 blank and 130.0 blank

**Style Designator:** 

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A047b0