

View Online at <https://aerobasegroup.com/nsn/5915-01-152-7151>

Overall Width:

0.656 inches

Body Length:

5.000 inches

Body Outside Diameter:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.875 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-20.0/+50.0 degrees celsius

Reference Frequency Per Function:

85.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

98291

Input Terminal Identification:

50-008-3196

Output Terminal Manufacturer Code:

98291

Output Terminal Identification:

50-008-3196

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

20.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 170.00 megahertz blank and 245.00 megahertz blank and 490.00 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

1.00 hertz blank and 170.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

130.0 megahertz blank and 170.0 megahertz blank

Special Features:

Wire leads with plug connectors

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0