

View Online at <https://aerobasegroup.com/nsn/5915-01-153-2618>

Overall Height:

0.779 inches

Body Length:

4.030 inches

Body Width:

2.280 inches

Body Height:

0.560 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.500 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Operating Temperature Range:

-29.0/+85.0 degrees celsius

Reference Frequency Per Function:

852.0 single high pass three phase to two phase

Source Impedance Rating Per Function:

1.0 kilohms 2nd band pass

Load Impedance Per Function:

100.0 kilohms 1st band pass 100.0 kilohms 2nd band pass 100.0 kilohms 3rd band pass 100.0 kilohms 4th band pass 100.0 kilohms 5th band pass

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd band pass 3rd function

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

14 pin

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 2nd band pass

Functional Terminal Type And Quantity:

5 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

747.00 hertz 4th band pass 4th function and 755.00 hertz 4th band pass 4th function and 785.00 hertz 4th band pass 4th function and 794.00 hertz 4th band pass 4th function

Body Material:

Metal

Frequency Band Width Per Function:

835.00 hertz 5th band pass and 869.00 hertz 5th band pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 3rd band pass 3rd function and 30.0 3rd band pass 3rd function

Body Surface Treatment:

Tin

Special Features:

Five filtered functions

Unpackaged Unit Weight:

4.250 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0