

View Online at <https://aerobasegroup.com/nsn/5915-01-153-7243>

**Overall Length:**

1.392 inches

**Body Outside Diameter:**

0.687 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

1.5 blank

**Maximum Voltage Drop Per Function:**

0.6 volts ac blank and 0.6 volts dc blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug input 1st function 1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

322.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac blank and 28.0 volts dc blank

**Thread Size:**

0.312 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Unpackaged Unit Weight:**

1.000 ounces

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0