

View Online at <https://aerobasegroup.com/nsn/5915-01-155-9600>

**Overall Length:**

4.725 inches

**Body Length:**

3.125 inches

**Body Outside Diameter:**

0.375 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

326.3 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

50140

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

50140

**Output Terminal Identification:**

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

312.40 megahertz blank and 319.35 megahertz blank and 333.25 megahertz blank and 340.20 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

319.35 megahertz blank and 333.25 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

319.35 megahertz blank and 333.25 megahertz blank

**Unpackaged Unit Weight:**

2.362 ounces

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0