

View Online at <https://aerobasegroup.com/nsn/5915-01-155-9871>

Overall Height:

7.650 inches

Body Length:

7.000 inches

Body Width:

3.000 inches

Body Height:

7.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.250 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-54.0/+90.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 2nd radio interference

Operating Current Rating Per Function In Amps:

25.0 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.001 and 0.02 and 0.07 and 0.5 and 1.0 and 10.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

4.0 and 20.0 and 40.0 and 60.0 and 60.0 and 60.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Functional Terminal Type And Quantity:

2 threaded stud input 1st function

Operating Voltage Rating And Type Per Function:

150.0 volts ac 2nd radio interference 2nd function and 450.0 volts dc 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

450.0 volts at sea level

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0