## NSN 5915-01-156-5703

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-156-5703

Overall Length:
4.780 inches
Overall Height:
1.030 inches
Body Length:
3.870 inches
Body Width:
2.400 inches
Unthreaded Mounting Hole Diameter:
0.193 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.375 inches
Vibration Resistance Range In Hertz:
+5.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.750 inches
Operating Tempurature Range:
-46.0/+49.0 degrees celsius
Reference Frequency Per Function:
312.5 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
2.1 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.00 hertz blank and 152.00 megahertz blank and 225.00 megahertz blank and 400.00 megahertz blank
Frequency Band Width Per Function:
225.00 megahertz blank and 400.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
50.0 blank and 50.0 blank and 3.0 blank and 3.0 blank
Voltage Standing Wave Ratio Frequency Limits Per Function:

225.0 megahertz blank and 400.0 megahertz blank

## NSN 5915-01-156-5703

High Pass Filter - Page 2 of 2



Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A047b0