

View Online at <https://aerobasegroup.com/nsn/5915-01-157-2791>

**Body Length:**

5.990 inches

**Body Width:**

0.750 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.150 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

6.375 inches

**Vibration Resistance Range In Hertz:**

+20.0/+2200.0

**Operating Temperature Range:**

-0.0/+55.0 degrees celsius

**Average Life Rating In Hours:**

2000.0

**Reference Frequency Per Function:**

227.5 7th radio interference pulses per second

**Source Impedance Rating Per Function:**

100.0 ohms 1st low pass

**Load Impedance Per Function:**

100.0 ohms 2nd low pass

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 1st low pass

**Functional Terminal Type And Quantity:**

2 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

9.00 kilohertz 2nd low pass and 12.00 kilohertz 2nd low pass and 15.00 kilohertz 2nd low pass and 500.00 megahertz 2nd low pass

**Frequency Band Width Per Function:**

9.00 kilohertz 2nd low pass and 12.00 kilohertz 2nd low pass

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 2nd low pass and 3.0 2nd low pass and 60.0 2nd low pass and 60.0 2nd low pass

**Maximum Dielectric Withstanding Dc Voltage:**

250.0 volts at sea level

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

16.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0