

View Online at <https://aerobasegroup.com/nsn/5915-01-157-2791>

Body Length:

5.990 inches

Body Width:

0.750 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.150 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

6.375 inches

Vibration Resistance Range In Hertz:

+20.0/+2200.0

Operating Temperature Range:

-0.0/+55.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

227.5 7th radio interference pulses per second

Source Impedance Rating Per Function:

100.0 ohms 1st low pass

Load Impedance Per Function:

100.0 ohms 2nd low pass

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 1st low pass

Functional Terminal Type And Quantity:

2 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

9.00 kilohertz 2nd low pass and 12.00 kilohertz 2nd low pass and 15.00 kilohertz 2nd low pass and 500.00 megahertz 2nd low pass

Frequency Band Width Per Function:

9.00 kilohertz 2nd low pass and 12.00 kilohertz 2nd low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 2nd low pass and 3.0 2nd low pass and 60.0 2nd low pass and 60.0 2nd low pass

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

16.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0