

View Online at <https://aerobasegroup.com/nsn/5915-01-158-4737>

**Overall Height:**

2.940 inches

**Body Length:**

4.500 inches

**Body Width:**

3.500 inches

**Body Height:**

1.620 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.875 inches

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 4th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 4th radio interference

**Operating Current Rating Per Function In Amps:**

7.0 2nd radio interference

**Principal Circuitry Type Per Function:**

Capacitance-inductance 4th radio interference

**Output Terminal Manufacturer Code:**

96906

**Output Terminal Identification:**

Ms3454w18-11p

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Functional Terminal Type And Quantity:**

1 tab, solder lug input 1st function1 connector, receptacle output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 1st radio interference 1st function115.0 volts ac 2nd radio interference 2nd function115.0 volts ac 3rd radio interference 3rd function115.0 volts ac 4th radio interference 4th function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1000.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0