

View Online at <https://aerobasegroup.com/nsn/5915-01-162-6214>

Overall Height:

0.560 inches

Body Length:

1.750 inches

Body Width:

0.750 inches

Body Height:

0.520 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.400 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.450 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

220.0 kilohertz blank

Source Impedance Rating Per Function:

150.0 ohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 terminal

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function 2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 220.00 kilohertz blank and 1.00 megahertz blank and 3.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 220.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 80.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0