

View Online at <https://aerobasegroup.com/nsn/5915-01-162-6333>

Overall Length:

5.260 inches

Body Length:

4.500 inches

Body Width:

1.250 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.300 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.050 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

5865-01-109-1689 signal processor

Reference Frequency Per Function:

2.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

57958

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

57958

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

15.0 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.70 megahertz blank and 1.90 megahertz blank and 2.10 megahertz blank and 2.30 megahertz blank

Thread Size:

0.112 inches

Body Material:

Aluminum

Frequency Band Width Per Function:

1.90 megahertz blank and 2.10 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.9 megahertz blank and 2.1 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0