NSN 5915-01-164-5667

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-164-5667

Overall Height:

1.380 inches

Body Length:

4.000 inches

Body Width:

2.000 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.400 inches

Operating Tempurature Range:

-10.0/+70.0 degrees celsius

End Application:

Radar system an/fps-117

Reference Frequency Per Function:

1.0 7th radio interference two phase to two phase

Source Impedance Rating Per Function:

50.0 ohms 2nd low pass

Load Impedance Per Function:

50.0 ohms 2nd low pass

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

10.0 2nd low pass

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz 2nd low pass and 3.50 megahertz 2nd low pass and 9.40 megahertz 2nd low pass and 11.00 megahertz 2nd low pass

Thread Size:

0.112 inches

Frequency Band Width Per Function:

1.00 hertz 2nd low pass and 3.50 megahertz 2nd low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 2nd low pass and 3.0 2nd low pass and 35.0 2nd low pass and 35.0 2nd low pass

NSN 5915-01-164-5667

Low Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0