

View Online at <https://aerobasegroup.com/nsn/5915-01-165-2969>

Body Length:

6.000 inches

Body Width:

1.250 inches

Body Height:

1.300 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

-35.0/+75.0 degrees celsius

End Application:

Test set, noise figure-comb generator an/wlr-6

Reference Frequency Per Function:

1.5 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

700.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank and 2.30 gigahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

1.00 gigahertz blank and 2.00 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 gigahertz blank and 2.0 gigahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0