NSN 5915-01-166-1908

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-166-1908

Overall Height:
4.780 inches
Body Length:
4.100 inches
Body Width:
1.000 inches
Body Height:
4.000 inches
Operating Tempurature Range:
-46.0/+71.0 degrees celsius
Reference Frequency Per Function:
875.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.3 blank
Average Power Rating Per Function:
1.0 kilowatts blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.3 blank
Functional Terminal Type And Quantity:
1 connector, receptacle input 1st function1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
665.00 megahertz blank and 770.00 megahertz blank and 980.00 megahertz blank and 1.085 gigahertz blank
Thread Size:
0.112 inches
Body Material:
Aluminum
Frequency Band Width Per Function:
771.00 megahertz blank and 980.00 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 50.0 blank

NSN 5915-01-166-1908

Band Pass Filter - Page 2 of 2

No Fiig: A047b0



Voltage Standing Wave Ratio Frequency Limits Per Function: 770.0 megahertz blank and 980.0 megahertz blank Body Surface Treatment: Silver Precious Material And Location: Body surfaces silver Precious Material: Silver Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: -Demilitarization: