

View Online at <https://aerobasegroup.com/nsn/5915-01-167-1612>

Overall Length:

1.660 inches

Body Outside Diameter:

0.250 inches

Operating Temperature Range:

-28.0/+72.0 degrees celsius

Reference Frequency Per Function:

2.5 hertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Input Terminal Manufacturer Code:

49956

Input Terminal Identification:

Sma-female

Output Terminal Manufacturer Code:

49956

Output Terminal Identification:

Sma-male

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 4.00 hertz blank and 20.00 hertz blank and 42.00 hertz blank

Frequency Band Width Per Function:

1.00 hertz blank and 4.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 4.0 hertz blank

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0