NSN 5915-01-167-3025

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-167-3025

| Body Length: |
|--|
| 2.000 inches |
| Body Width: |
| 2.250 inches |
| Body Height: |
| 4.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.500 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+500.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.750 inches |
| Operating Tempurature Range: |
| -0.0/+70.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Power Line Frequency Rating Per Function In Hertz: |
| 60.0 blank |
| Operating Current Rating Per Function In Amps: |
| 2.0 blank |
| Maximum Voltage Drop Per Function: |
| 1.0 volts ac blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Input Terminal Manufacturer Code: |
| 96906 |
| Input Terminal Identification: |
| Ms3402d10sl-3p |
| Maximum Tempurature Rise: |
| 25.0 degrees celsius |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Functional Terminal Type And Quantity: |
| 2 pin output 2nd function |

130.0 volts ac blank

Operating Voltage Rating And Type Per Function:

NSN 5915-01-167-3025

Radio Frequency Interference Filter - Page 2 of 2



| Thread Size: |
|---|
| 0.164 inches |
| Body Material: |
| Metal |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A047b0