

View Online at <https://aerobasegroup.com/nsn/5915-01-167-8174>

**Body Length:**

Between 4.470 inches and 4.530 inches

**Body Width:**

Between 2.970 inches and 3.030 inches

**Body Height:**

Between 4.970 inches and 5.030 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-40.0/+90.0 degrees celsius

**Average Life Rating In Hours:**

250.0

**End Application:**

Test set, countermeasure an/usm-464

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 4th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

420.0 4th radio interference

**Operating Current Rating Per Function In Amps:**

15.0 3rd radio interference

**Maximum Voltage Drop Per Function:**

0.5 volts ac 4th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference

**Maximum Temperature Rise:**

30.0 degrees celsius

**Inclosure Type:**

Encased

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

8 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 4th radio interference 4th function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.5 kilovolts at sea level

**Body Surface Treatment:**

Tin

**Unpackaged Unit Weight:**

6.800 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0