

View Online at https://aerobasegroup.com/nsn/5915-01-170-0508

Overall Length:

Between 1.202 inches and 1.326 inches

Body Length:

0.493 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

1000.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

10.0 blank

Maximum Voltage Drop Per Function:

0.1 volts ac blank and 0.1 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Tempurature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Width Across Flats:

Between 0.177 inches and 0.197 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 wire lead output 2nd function

Operating Voltage Rating And Type Per Function:

70.0 volts ac blank and 100.0 volts dc blank

Thread Size:

0.216 inches

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Body Surface Treatment:

Silver



Unpackaged Unit Weight:

2.0 grams

Precious Material And Location:

Body surfaces silver

Precious Material:

Silver

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/61 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Eiia

Fiig:

A047b0