

View Online at <https://aerobasegroup.com/nsn/5915-01-170-0509>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

2.8 gigahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

0.6 blank

Specified Frequencies Of Discrimination Per Function:

454.00 megahertz blank and 5.40 gigahertz blank and 10.00 gigahertz blank and 10.50 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

454.00 megahertz blank and 5.40 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 50.0 blank and 10.50 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

454.0 megahertz blank and 5.4 gigahertz blank

Maximum Dielectric Withstanding Dc Voltage:

400.0 volts at sea level

Unpackaged Unit Weight:

30.0 grams

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0