

View Online at <https://aerobasegroup.com/nsn/5915-01-171-5725>

**Overall Length:**

1.233 inches

**Body Length:**

0.384 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

0.1 volts ac blank and 0.1 volts dc blank

**Principal Circuitry Type Per Function:**

Capacitance-inductance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Width Across Flats:**

0.202 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 wire lead output 2nd function

**Operating Voltage Rating And Type Per Function:**

70.0 volts ac blank and 100.0 volts dc blank

**Thread Size:**

0.164 inches

**Maximum Dielectric Withstanding Dc Voltage:**

2.5 kilovolts at sea level

**Body Surface Treatment:**

Silver

**Unpackaged Unit Weight:**

2.2 grams

**Precious Material And Location:**

Body surface silver

**Precious Material:**

Silver

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Test Data Document:**

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-15733/61 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0