Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-174-1164

Overall Length:
1.130 inches
Body Length:
0.690 inches
Body Outside Diameter:
0.375 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
10.0 blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
1 tab, solder lug output 2nd function
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 400.0 volts at sea level
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 400.0 volts at sea level Style Designator:
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 400.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces
1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Maximum Dielectric Withstanding Dc Voltage: 400.0 volts at sea level Style Designator: Round terminal/terminals on opposite surfaces Shelf Life:



Demilitarization:

Yes - demil/mli

Fiig:

A047b0