

View Online at <https://aerobasegroup.com/nsn/5915-01-175-8326>

Overall Length:

Between 0.395 inches and 0.405 inches

Body Length:

0.305 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

424.0 blank

Operating Current Rating Per Function In Amps:

15.0 blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

75.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Width Across Flats:

0.191 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 pin output 2nd function

Operating Voltage Rating And Type Per Function:

85.0 volts ac blank and 125.0 volts dc blank

Thread Size:

0.164 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

375.0 volts at sea level

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

0.4 grams

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/44 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0