

View Online at <https://aerobasegroup.com/nsn/5915-01-178-4277>

Overall Length:

8.750 inches

Body Outside Diameter:

1.130 inches

Vibration Resistance Range In Hertz:

+0.02/+2000.00

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

900.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

21377

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

21377

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

525.00 megahertz blank and 837.50 megahertz blank and 962.50 megahertz blank and 1.275 gigahertz blank

Frequency Band Width Per Function:

837.50 megahertz blank and 962.50 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

837.5 megahertz blank and 962.5 megahertz blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0