

View Online at <https://aerobasegroup.com/nsn/5915-01-181-6625>

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-0.0/+70.0 degrees celsius

**End Application:**

Jtidsasiturq3

**Reference Frequency Per Function:**

200.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 connector, plug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 400.00 megahertz blank and 1.255 gigahertz blank and 2.00 gigahertz blank

**Frequency Band Width Per Function:**

1.00 hertz blank and 400.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 400.0 megahertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0