

View Online at <https://aerobasegroup.com/nsn/5915-01-181-6625>

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-0.0/+70.0 degrees celsius

End Application:

Jtidsasiturq3

Reference Frequency Per Function:

200.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 connector, plug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 400.00 megahertz blank and 1.255 gigahertz blank and 2.00 gigahertz blank

Frequency Band Width Per Function:

1.00 hertz blank and 400.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 400.0 megahertz blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0