

View Online at https://aerobasegroup.com/nsn/5915-01-183-6390

Overall Length:
1.700 inches
Body Length:
0.952 inches
Body Outside Diameter:
0.690 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
5.0 ohms blank
Load Impedance Per Function:
5.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
1.5 blank
Principal Circuitry Type Per Function:
Inductance-capacitance, mounting end blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Inclosure Type: Hermetically sealed
Hermetically sealed
Hermetically sealed Mounting Facility Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Unpackaged Unit Weight:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Unpackaged Unit Weight: 30.0 grams
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Unpackaged Unit Weight: 30.0 grams Style Designator:
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 125.0 volts ac blank Thread Size: 0.312 inches Body Material: Metal Unpackaged Unit Weight: 30.0 grams Style Designator: Round terminal/terminals on opposite surfaces



Demilitarization:

No

Fiig:

A047b0