

View Online at <https://aerobasegroup.com/nsn/5915-01-184-5350>

Overall Length:

1.719 inches

Overall Height:

1.032 inches

Body Length:

1.125 inches

Body Width:

1.000 inches

Body Height:

0.688 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.438 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

0.1 blank

Maximum Voltage Drop Per Function:

3.0 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 0.15 and 1.0 and 10.0 and 100.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

27.0 and 45.0 and 53.0 and 58.0 and 61.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

1 tab, solder lug input 1st function 1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

300.0 volts dc blank

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

600.0 volts at sea level

Unpackaged Unit Weight:

2.000 ounces

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0