

View Online at <https://aerobasegroup.com/nsn/5915-01-189-3175>

Body Length:

7.250 inches

Body Width:

4.030 inches

Body Height:

0.750 inches

Vibration Resistance Range In Hertz:

+4.0/+25.0

Operating Temperature Range:

-0.0/+65.0 degrees celsius

End Application:

Mk72m15 sdc

Reference Frequency Per Function:

5.6375 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.2 blank

Average Power Rating Per Function:

1.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.3 blank

Functional Terminal Type And Quantity:

1 rectangular flange input 1st function

Specified Frequencies Of Discrimination Per Function:

6.11 gigahertz blank and 5.45 gigahertz blank and 5.825 gigahertz blank and 7.147 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

5.45 gigahertz blank and 5.825 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 blank and 3.0 blank and 3.0 blank and 55.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

5.45 gigahertz blank and 5.825 gigahertz blank

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

3.000 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0