

View Online at <https://aerobasegroup.com/nsn/5915-01-189-3177>

Overall Length:

11.685 inches

Mounting Slot Width:

Between 0.250 inches and 0.260 inches

Body Length:

Between 9.970 inches and 10.030 inches

Body Width:

7.060 inches

Body Height:

4.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 5.990 inches and 6.010 inches

Operating Temperature Range:

-0.0/+70.0 degrees celsius

Average Life Rating In Hours:

10000.0

End Application:

Mk72m15 sdc

Source Impedance Rating Per Function:

50.0 ohms 3rd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 3rd radio interference

Operating Current Rating Per Function In Amps:

35.0 3rd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3406d22-22sx

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

6 threaded hole

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

3 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 3rd radio interference 3rd function

Thread Size:

0.190 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

Three filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0