

View Online at <https://aerobasegroup.com/nsn/5915-01-189-3178>

Overall Length:

8.650 inches

Body Length:

7.000 inches

Body Width:

5.060 inches

Body Height:

2.310 inches

Unthreaded Mounting Hole Diameter:

Between 0.286 inches and 0.295 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-0.0/+70.0 degrees celsius

Average Life Rating In Hours:

10000.0

End Application:

Mk72m15 sdc

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

25.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

30.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 20.0 and 80.0 and 80.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

2 threaded stud output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.190 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

900.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0