

View Online at <https://aerobasegroup.com/nsn/5915-01-190-6746>

**Overall Height:**

5.010 inches

**Body Length:**

5.500 inches

**Body Width:**

4.500 inches

**Body Height:**

3.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.735 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.735 inches

**Operating Temperature Range:**

-0.0/+70.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**End Application:**

Mk72m15 sdc

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Operating Current Rating Per Function In Amps:**

5.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

0.5 volts dc 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

110.0 degrees celsius

**Average Power Rating Per Function:**

3.0 watts 2nd radio interference

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

3.0 and 65.0 and 80.0 and 80.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Functional Terminal Type And Quantity:**

2 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

50.0 volts dc 2nd radio interference 2nd function

**Thread Size:**

0.250 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0