

View Online at <https://aerobasegroup.com/nsn/5915-01-190-6747>

Overall Length:

3.500 inches

Body Outside Diameter:

0.630 inches

Vibration Resistance Range In Hertz:

+4.0/+25.0

Operating Temperature Range:

-0.0/+65.0 degrees celsius

End Application:

Mk72m15 sdc

Reference Frequency Per Function:

5.7 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

53711

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

53711

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.2 blank

Average Power Rating Per Function:

50.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

5.40 gigahertz blank and 6.00 gigahertz blank and 10.80 gigahertz blank and 21.60 gigahertz blank

Frequency Band Width Per Function:

5.40 gigahertz blank and 6.00 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 22.0 blank and 22.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

5.4 gigahertz blank and 6.0 gigahertz blank

Unpackaged Unit Weight:

4.000 ounces

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0