NSN 5915-01-192-7793

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-192-7793

Body Length:
2.100 inches
Body Width:
1.600 inches
Body Height:
0.670 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-0.0/+65.0 degrees celsius
End Application:
An/wlq- (v)
Reference Frequency Per Function:
750.0 hertz blank
Source Impedance Rating Per Function:
1.0 kilohms blank
Load Impedance Per Function:
3.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
g,
Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Encased
Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank Thread Size:
Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank Thread Size: 0.138 inches
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank Thread Size: 0.138 inches Body Material:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank Thread Size: 0.138 inches Body Material: Metal
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 1.50 kilohertz blank and 6.25 kilohertz blank and 12.50 kilohertz blank Thread Size: 0.138 inches Body Material: Metal Frequency Band Width Per Function:

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-01-192-7793

Low Pass Filter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0