

View Online at <https://aerobasegroup.com/nsn/5915-01-192-8563>

Operating Temperature Range:

-0.0/+71.0 degrees celsius

Reference Frequency Per Function:

350.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Terminal Manufacturer Code:

17903

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

17903

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.35 blank

Average Power Rating Per Function:

1.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.4 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 750.00 megahertz blank and 2.30 gigahertz blank and 4.60 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 750.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 70.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 hertz blank and 750.0 megahertz blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0