

View Online at <https://aerobasegroup.com/nsn/5915-01-192-8563>

**Operating Temperature Range:**

-0.0/+71.0 degrees celsius

**Reference Frequency Per Function:**

350.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

17903

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

17903

**Output Terminal Identification:**

Sma-receptacle

**Voltage Standing Wave Ratio Per Function:**

1.35 blank

**Average Power Rating Per Function:**

1.0 watts blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.4 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 750.00 megahertz blank and 2.30 gigahertz blank and 4.60 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 750.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 70.0 blank and 70.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 hertz blank and 750.0 megahertz blank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0