

View Online at <https://aerobasegroup.com/nsn/5915-01-192-8671>

**Overall Length:**

5.900 inches

**Overall Height:**

1.750 inches

**Body Length:**

5.000 inches

**Body Width:**

1.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.000 inches

**Vibration Resistance Range In Hertz:**

+5.0/+25.0

**Operating Temperature Range:**

-0.0/+85.0 degrees celsius

**End Application:**

Receiving set, countermeasures an/wlq- (v)

**Reference Frequency Per Function:**

455.0 kilohertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

07397

**Output Terminal Manufacturer Code:**

07397

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

7.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

431.00 kilohertz blank and 443.50 kilohertz blank and 466.50 kilohertz blank and 479.00 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

443.50 kilohertz blank and 466.50 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

443.5 kilohertz blank and 466.5 kilohertz blank

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0