## NSN 5915-01-193-5218

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-193-5218

**Overall Height:** 

2.410 inches

**Body Length:** 

Between 2.570 inches and 2.630 inches

**Body Width:** 

Between 2.320 inches and 2.380 inches

**Body Height:** 

1.650 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.115 inches and 2.135 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.865 inches and 1.885 inches

**Operating Tempurature Range:** 

-55.0/+85.0 degrees celsius

#### **Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

#### **Load Impedance Per Function:**

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

## **Power Line Frequency Rating Per Function In Hertz:**

400.0 1st radio interference400.0 2nd radio interference400.0 3rd radio interference

#### **Operating Current Rating Per Function In Amps:**

3.0 1st radio interference3.0 2nd radio interference3.0 3rd radio interference3.0 4th radio interference2.0 5th radio interference1.0 6th radio interference

## **Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

#### **Mounting Facility Screw Thread Series Designator:**

Unc

## Inclosure Type:

Hermetically sealed

#### **Mounting Facility Type And Quantity:**

4 threaded hole

#### **Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function8 solder stud output 2nd function

### **Operating Voltage Rating And Type Per Function:**

115.0 volts ac 1st radio interference 1st function115.0 volts ac 2nd radio interference 2nd function115.0 volts ac 3rd radio interference 3rd function28.0 volts dc 4th radio interference 4th function28.0 volts dc 5th radio interference 5th function28.0 volts dc 6th radio interference 6th function

## **Thread Size:**

0.138 inches

## **Body Material:**

Metal

Special Features:

# NSN 5915-01-193-5218

Radio Frequency Interference Filter - Page 2 of 2



|--|

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0